



J. M. Engineering Co.

A collage of images related to engineering and manufacturing, including a blue and white airplane, various colored heat shrink sleeves, rolls of yellow and green sleeves, a circuit board, and wind turbines. A yellow square is positioned behind the word 'PRODUCTS'.

PRODUCTS

Heat Shrink Sleeves

Skid Proof Heat Shrink Sleeves



Visit Us

Manhar Bldg., 3rd Floor, 177,
Lohar Chawl, Mumbai –
400002, Maharashtra (INDIA)



Email Us

info@jmenggco.in



Call Us

T: +91-22-2206 1671
F: +91-22-2209 0291



WOLVO

Skidproof Heat Shrink Tubing

Polyolefin tubing with skidproof figured surface, used for various fishing tackles, sport fittings, and equipments and commodities with hand device.



Features

- Good abrasion resistant and anti-skid performance
- High flexibility
- Quick installation
- Continuous operating temperature: -55 - 125
- Shrink temperature: started at 70 , full recovery at 110
- Standard color: Black, Red, Yellow, Green, Blue



Dimensions

Size mm	Expanded		After Recovery		Standard Package M/pc
	Internal Diameter mm	Wall Thickness mm	Internal Diameter mm	Wall Thickness mm	
15	15	0.45±0.15	8.0	0.85±0.15	1.0
18	18	0.45±0.15	10.0	0.85±0.15	1.0
20	20	0.50±0.15	11.0	0.90±0.15	1.0, 1.6
22	22	0.50±0.15	12.5	0.90±0.15	1.0, 1.6
25	25	0.50±0.15	14.5	1.00±0.15	1.0, 1.6
28	28	0.50±0.15	15.5	1.00±0.15	1.0, 1.6
30	30	0.60±0.15	17.5	1.20±0.15	1.0, 1.6
35	35	0.60±0.15	20.0	1.20±0.15	1.0, 1.6
40	40	0.60±0.15	23.0	1.20±0.15	1.0, 1.6
45	45	0.65±0.15	25.0	1.25±0.15	1.0, 1.6
50	50	0.65±0.15	28.0	1.25±0.15	1.0, 1.6

Technical Data

Property	Test Method	Typical Performance
Tensile Strength(MPa)	ASTM D2671	10.4
Elongation(%)	ASTM D2671	200